



NU-CRYL AG

Anti-Graffiti for Vertical Porous Surfaces

Clear and lasting protection

USES

Nu-Cryl AG a unique, clear, hydrophobic acrylic coating which gives long life anti graffiti and environmental protection for all porous building material: brickwork, concrete, natural stone, reconstructed stone and block work. It can be used on concrete that has been treated with most types of impregnates. This product satisfies Class'0' requirements of current Building Regulation.

A single application is normally sufficient to give protection for up to 15 years due to its outstanding resistance to weathering and ultra-violet degradation. On porous substrates a second application maybe required and this should be applied immediately after the first application (wet on wet). Dirt, pollution and graffiti can be repeatedly removed from the treated surface without reducing the protection quality of the coating.


COVERAGE	3-5m ² /L depending on substrate type.
CURING TIME	Touch dry 4 hours Fully dry 24 hours Allow 72hrs before treating with Silane.
APPLICATION	Low pressure spray, brush or roller.
PACKAGE	5L and 25L drums
SHELF LIFE	12 months in original sealed container
STORAGE	Away from direct sunlight and sources of heat. protect from frost.

PRODUCT OVERVIEW



BENEFITS

- Repeatedly cleanable
- Invisible protection
- Suitable for all porous building materials
- Single application
- Fast cure
- Meets Class 'O' requirements
- Protects for up to 15 years
- Solvent free



Concrete & Asphalt
Protection & Maintenance
Consultancy & Products

www.dantexltd.com

Dantex Ltd
Communications House
26 York Street London W1U 6PZ
E: enquiries@dantexltd.com
T: +44(0)207 873 2188
F: +44(0)207 112 8010