



# CRETE-PRIME

## Primer for Concrete

### USES

Crete-Prime is a single pack solvent based primer designed for use on prepared concrete surfaces. It is a high quality thin resin/rubber solution for priming surfaces prior to the application of the following Dantex surface maintenance products: Maxi-Flex, Maxi-Crete, Maxi-Screed, Ultra-Band and Ultra-Screed.

### APPLICATION OVERVIEW

The surface must be dry and free of dust, salts, grease and other contaminants immediately before coating. Performance of Crete-Prime will be greatly enhanced by a high standard of surface preparation. Brush or spray application is preferred on all prepared surfaces.

Application of Crete-Prime is by brush or spray.

By brush, apply evenly using a clean, well-loaded brush. Do not attempt to "brush out" the wet coating. At all times avoid ponding or over application of the primer.

By spray, apply a light 'mist' coat to all surfaces until fully covered and allow to cure.

Only fully trained operatives must be allowed to apply Crete-Prime.

## TECHNICAL DATA

COLOUR	Red
FORM	Liquid
FLASHPOINT	Approx.. 0°C
APPLICATION TEMP. RANGE	5°C -80°C
CURING/DRYING	Tack dry 10-15mins
PACKAGING	5ltr AND 10ltr
STORAGE TEMP. RANGE	0°C -45°C
SHELF LIFE	12 months

### WARRANTY

The Company warrants that the materials meet stated specifications at the time dispatched from factory. Techniques used for the preparation of the repair prior to application are beyond our control, as are the use and application of the materials. The Company shall not be responsible for improperly applied or misused materials. There shall be no other warranties expressed or implied.



Concrete & Asphalt  
Protection & Maintenance  
Consultancy & Products

[www.dantexltd.com](http://www.dantexltd.com)

Dantex Ltd  
Communications House  
26 York Street London W1U 6PZ  
E: [enquiries@dantexltd.com](mailto:enquiries@dantexltd.com)  
T: +44(0)207 873 2188  
F: +44(0)207 112 8010